



REDUCE YOUR PUSH/PULL FORCE, DECREASING WORK PLACE INJURIES,

WITH OUR NEW **“LOADMASTER”** CASTER.

WHERE HIGH PERFORMANCE MEETS ERGONOMICS!

See comparison data on back side of flyer, Loadmaster verse Standard Phenolic and Polyurethane tread wheels.

CASTER SPECIFICATIONS:

- SEALED PRECISION, MAINTENANCE FREE RACEWAY
- INDUSTRY STANDARD 4 X 4½ TOP PLATE
- SUPERIOR PERFORMANCE, HIGH CAPACITY, MACHINED NYLATRON WHEEL WITH A SLIGHTLY CROWNED TREAD
- TEMPERATURE RANGE: -30 °F TO +220 °F
- HARDNESS: 80(±5) DUROMETER SHORE D SCALE
- ALL 2” WIDE CASTERS HAVE A CAPACITY 1250 LBS

PRICE:

	4 X 2	5 X 2	6 X 2	8 X 2
RIGID	\$52.65	\$69.71	\$79.53	\$88.86
SWIVEL	\$73.94	\$91.40	\$99.57	\$109.23



CENTRAL STATES CASTERS

3100 North Roemer Road
Appleton, WI 54911 | Ph: (800) 735-6659

[email: Sales@CSCcaster.com](mailto:Sales@CSCcaster.com) www.csccaster.com



PULL FORCE - IN LINE		PULL FORCE - AT 90°		PULL FORCE - AT 180°		AVERAGE REDUCTION OF FORCE WHEN UPGRADING TO THE "LOADMASTER" CASTER
Initial	Max	Initial	Max	Initial	Max	

SEALED PRECISION BEARING RACEWAY WITH SOLID ELASTOMER WHEEL	10.4	32.2	26.9	43.9	11.1	37.7	29.86%
---	------	------	------	------	------	------	---------------

SEALED PRECISION BEARING RACEWAY WITH PHENOLIC WHEEL	15.7	36.9	17.2	38.5	15.1	37.3	33.36%
--	------	------	------	------	------	------	---------------

SEALED PRECISION BEARING RACEWAY WITH POLYURETHANE TREAD	47.1	62.2	61.2	78.4	50.9	69.4	70.79%
--	------	------	------	------	------	------	---------------

SEALED PRECISION BEARING RACEWAY WITH HEAVY DUTY NYLATRON WHEEL	7.3	23.5	10.9	29.2	8.7	34.7	OUR NEW LOADMASTER CASTER
---	------------	-------------	-------------	-------------	------------	-------------	-------------------------------------

* ALL TEST RESULTS BASED ON CART WEIGHT OF 2,000 LBS IN STANDARD WAREHOUSE CONDITIONS